

Digital Display Asphalt Ductilometer (Ductility Testing Machine)



STYD-2 Digital Display Asphalt Ductilometer

Application:

1. Determination of ductility and the elastic reset of bitumen.
2. Stainless steel for both casing and water bath.

Parameters:

1. Extension Speed: 50 ± 2.5 mm/min
2. Max. Ductility: 1500mm, 2000mm
3. Heating Range: Room temperature -50°C
4. Temperature accuracy: ± 0.5 °C
5. Voltage: AC220V 50HZ
6. Mold size: 75×32×10mm
7. Suitable for Testing 3 Samples Simultaneously
8. Dimension: 2080×390×560mm
9. G.W/N.W (Kgs): 175/150 Kgs

Features:

1. Stainless steel for both inside and outside casing
2. With ABS controller
3. And twin lead screws



SPECIFICATION :

Model No.	STYD-2
Mass Scope of Workpiece	<900kg
Display	Digital
Weight	175kg
Heating Range	Room Temperature-50c
Mould Size	75X32X10mm
Dimension	75X32X10mm
Dimension	1.31CBM
Max Diameter of Workpiece	<500mm
Type	Asphalt Test Apparatu
Accuracy Grade	1
Control	Digital Display
Power Source	AC220V
Max. Ductility	1500mm, 2000mm
Voltage	AC220V 50Hz
Suitable for	Testing 3 Samples Simutaneously
Features	Stainless Steel for Both Inside and Outside Casing
Extension speed	50±2.5mm/min
Max. ductility	1500mm, 2000mm
Heating range	room temperature-50°C
Temperature accuracy	±0.5°C
Mould size	75×32×10mm
Suitable	for testing 3 samples simutaneously
Dimension	2080×390×560mm

A.K. Bhuiyan & Co.

28/A, Murad Road, (Avoy Das Lane), Tikatuly, Dhaka-1203

Tel: 02-47115236, Mob: 01819-281414, 01801830199627, 01303190326